



Number	18GR0384/00	Contract number	E 7660
Issue date	21-04-2018	Scope	(EU) 2016/426 (9 March 2016)
Due date	27-03-2028	Module	B (Type testing)
PIN	0063CT1313	Report number	1711013131

EU TYPE EXAMINATION CERTIFICATE (GAR)

Kiwa hereby declares that the manually operated taps, type(s):

**GA,
GN,
KF,
MA,
PGN,
PKF,
PMA**

manufactured by

**Turaş Gaz Armatürleri Sanayi ve Ticaret
Anonim Şirketi
Silivri/İstanbul, TÜRKİYE**

meet(s) the essential requirements as described in the
Regulation (EU) 2016/426 relating to appliances burning gaseous fuels.

The compliance is based on examination to EN 1106:2010.

The product(s) has/have been approved for all EU and EFTA countries.

A description of the specific types is given in the appendix to this certificate.

Luc Leroy, Kiwa



Number	18GR0384/00	Page	1 of 1
Issue date	21-04-2018	Scope	(EU) 2016/426 (9 March 2016)
Due date	27-03-2028	Module	B (Type testing)
PIN	0063CT1313	Report number	1711013131

APPENDIX TO EU TYPE EXAMINATION CERTIFICATE (GAR)

PRODUCT INFORMATION

Non-safety valves group:

Types GN, PGN, GA

Manually operated gas valves

Trade mark:	GN – GA – PGN
GN	manually operated brass gas valve for ovens
PGN	manually operated aluminium gas valve for ovens
GA	Manually operated brass gas valve for table top hobs

Group:	1
Gas families:	I, II, III
Max. working pressure:	65 mbar
Nominal diameter:	DN 6
Min/max. working temperature:	0 °C – 130 °C
Number of outlets:	1
Flow rate:	0.60 m ³ /hr
Opening angle (max. flow rate):	90 °
Opening angle (min. flow rated):	160 °

Types KF, PKF, MA, PMA

Manually operated gas valves

Trade mark:	KF – PKF - MA – PMA
KF	Manually operated brass gas valve for ovens
PKF	Manually operated aluminium gas valve for ovens
MA	Manually operated gas valve for table top hobs
PMA	Manually operated aluminium gas table top hobs

Group:	1
Gas families:	I, II, III
Max. working pressure:	65 mbar
Nominal diameter:	DN 6
Min/max. working temperature:	0 °C – 130 °C
Number of outlets:	1
Flow rate:	0.60 m ³ /hr
Opening angle (max. flow rate):	90 °
Opening angle (min. flow rated):	160 °